

Ubiquiti AirOS 2.4Ghz Product Inter-Operation Matrix 14 Apr 10

| STATION | Bullet 2 / 2HP | Bullet M2 | NanoStation 2 / 2 Loco | NanoStation M2 | PicoStation 2 / 2HP | Rocket M2 | PowerStation 2 |
|-------------------------------|----------------|-----------|------------------------|----------------|---------------------|-----------|----------------|
| ACCESS-POINT | | | | | | | |
| Bullet 2 / 2HP | I | I | I | I | I | I | I |
| Bullet M2 | I | GH | I | GH | I | GH | I |
| NanoStation 2 / 2 Loco | I | I | I | I | I | I | I |
| NanoStation M2 | I | GH | I | CD | I | CD | I |
| PicoStation 2 / 2HP | I | I | I | I | I | I | I |
| Rocket M2 | I | EF | I | AB | I | AB | I |
| PowerStation 2 | I | I | I | I | I | I | I |

- A:** AirMAX on; 'N' mode; MIMO 2X2 compatible; max. MCS14 data rate; max. 40Mhz channel width; max. 120 users per AP radio [64Mb RAM]
- B:** AirMAX off; 'N' mode; MIMO 2X2 compatible; max. MCS14 data rate; max. 40Mhz channel width; max. 60 users per AP radio [64Mb RAM]
- C:** AirMAX on; 'N' mode; MIMO 2X2 compatible; max. MCS14 data rate; max. 40Mhz channel width; max. 60 users per AP radio [32Mb RAM]
- D:** AirMAX off; 'N' mode; MIMO 2X2 compatible; max. MCS14 data rate; max. 40Mhz channel width; max. 35 users per AP radio [32Mb RAM]
- E:** AirMAX on; 'N' mode; MIMO 1X1 compatible; max. MCS7 data rate; max. 40Mhz channel width; max. 120 users per AP radio [64Mb RAM]
- F:** AirMAX off; 'N' mode; MIMO 1X1 compatible; max. MCS7 data rate; max. 40Mhz channel width; max. 60 users per AP radio [64Mb RAM]
- G:** AirMAX on; 'N' mode; MIMO 1X1 compatible; max. MCS7 data rate; max. 40Mhz channel width; max. 60 users per AP radio [32Mb RAM]
- H:** AirMAX off; 'N' mode; MIMO 1X1 compatible; max. MCS7 data rate; max. 40Mhz channel width; max. 35 users per AP radio [32 Mb RAM]
- I:** AirMAX off or not available; 'b/g' modes only; 5, 10 or 20 data rate; max 20Mhz channel width; max. 35 users per AP radio